



## ST. TAMMANY PARISH

PATRICIA P. BRISTER  
PARISH PRESIDENT

**October 3, 2018**

Please find the following addendum to the below mentioned QUOTE.

**Addendum No.:** 2

**Quote#:** 312-00-18-26-1

**Project Name:** Windsor Dr. Drainage

**Quote Due Date:** Monday, October 15, 2018

### **GENERAL INFORMATION:**

---

1. Please note that the Quote Opening has been pushed to Monday, October 15, 2018. Time and location remains the same. The last day for Addendum is October 10, 2018 at 2:00pm.
2. Please remove "Attachment A – Specifications-REVISED" and replace with "Attachment A – Specifications REVISED 01." (Attached)

### **ATTACHMENTS:**

---

1. "Attachment A – Specifications REVISED 01.pdf"

**End of Addendum # 2**

Starting at Sta. 00+00 at intersection of Ab's Rd. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description   | Length | Width | Quantity | Unit     |
|--------|---|--------|-------|----------|----------|
|        | <p><b>General Notes:</b></p> <ol style="list-style-type: none"> <li>1. Contractor shall field verify all quantities and measurements.</li> <li>2. Contractor shall be responsible for locating and protecting all existing utilities.</li> <li>3. Two-way traffic shall be maintained at all times during construction.</li> <li>4. Prior to beginning work, contractor shall furnish, erect and maintain project and construction signs in accordance with LA DOTD Standard Plans and Special Details Temporary Traffic Control.</li> <li>5. Driveway aprons shall be tied-in to existing hard surfaced drives or extend two (2) feet behind the culvert, whichever is greater. For clarification purposes, tie-in new asphalt to existing asphalt/concrete aprons at no direct pay.</li> <li>6. All turning radii shall be a minimum of thirty-five (35) feet.</li> <li>7. All existing sewer lines shall be tied-in at no direct pay.</li> <li>8. For clarification purposes, tie-in new asphalt to existing asphalt aprons at no direct pay on existing gravel roads.</li> <li>9. Any <i>additional work</i> performed by the contractor <i>without prior written approval</i> from the St Tammany Parish Department of Public Works, the cost of the work will be borne by the contractor and will not be reimbursed by the Parish.</li> </ol> |        |       |          |          |
|        | <p><b>Project Summary:</b> All labor and materials necessary to improve drainage by removing the existing culverts and replacing them with new culverts or trench drain at correct elevations as shown in the project drawings. Work shall also include replacing the drives with either asphalt or concrete, install 2 headwalls, sod at end of pipes and grade, shape, compact and pave end of street with (2) 2" lifts of asphalt.</p>   |        |       |          |          |
| 727-01 | <p><b>Mobilization:</b> All labor and materials necessary to accomplish preparatory work and operations, including those necessary for movement of personnel, equipment, supplies and incidentals to the project site.</p>  |        |       | 1        | Lump Sum |
| 713-01 | <p><b>Temporary Signs and Barricades:</b> All labor and materials necessary to furnish, install, maintain and remove temporary project signs, construction signs and/or barricades; providing flagmen; and complying with all other requirements regarding the protection of the work, workers and safety of the public. All items shall comply with plan details.</p> <p>All signs must be up prior to work starting for item to be paid.</p>  |        |       | 1        | Lump Sum |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition

Starting at Sta. 00+00 at intersection of Ab's Rd. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description   | Length   | Width     | Quantity | Unit        |
|--------|---|--|-----------|----------|-------------|
| 306-01 | <b>Grade, Shape and Compact Road Bed:</b> Labor and materials necessary to grade, shape and compact existing gravel road to prepare for asphalt paving. Work shall include removal of excess rock to install base at correct elevation to receive 4" of asphalt paving. All work shall be done in accordance with the LA DOTD Standard Specifications for Roads and Bridges, Sec. 306, 2016 Edition. All debris shall be removed at no direct pay.  |  |           | 68       | Square Yard |
| 501-03 | <b>2" Asphalt Paving (LA DOTD Type 3):</b> All labor and materials necessary to provide and install 4" asphalt paving in 2 lifts. The contractor shall grade, shape and compact the existing stone base to allow for the installation of paving. All work shall be done in accordance with the LA DOTD Standard Specifications for Roads and Bridges, Section 501, 2000 Edition. The contractor shall saw cut along the existing edge of the pavement to provide a smooth, straight edge to pave along. All debris is to be removed at no direct pay.   | 1 <sup>st</sup> . 2" lift<br>2 <sup>nd</sup> 2" lift |           | 68<br>68 | Square Yard |
| 501-01 | <b>3" Asphalt Drive (LA DOTD Type 3):</b> All labor and materials necessary to install Asphalt driveway aprons and tie ins to existing drives. Driveway aprons on gravel/dirt drives shall be tied-in to existing hard surfaced drives or extend to the back edge of the ditch, whichever is greater. Aprons are to be installed per the LA DOTD Rural Drive Detail. Existing asphalt drives shall receive a new topping of asphalt and be extended to the back edge of the ditch if necessary. Transition aprons onto existing concrete drives are to be 18" minimum and shall be sealed where the edge tapers down to the existing hard surface drive to prevent unraveling. Sealer shall be applied with either a brush or roller and shall be 6' wide with three inches extending over the apron and three inches over the existing hard surface. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Section 501, 2000 Edition. All debris shall be removed at no direct pay. | 3 drives   | See Plans | 12       | Ton         |
| 706-03 | <b>6" Concrete Drive:</b> All labor and materials necessary to remove and replace existing concrete drive. The drive is to be constructed of 3000 psi Type M "High Early, 72hr mix" concrete, 6" thick and shall have fiber mesh. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Section 706, 2016 Edition. All joint material shall be in kind and sealed with a product listed in the QPL. Work shall include all necessary saw cuts to remove the drive way panel. All debris shall be removed at no direct pay.   | 9 drives   | See Plans | 295      | Square Yard |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition

Starting at Sta. 00+00 at intersection of Ab's Rd. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description  | Length | Width | Quantity | Unit        |
|--------|--|--------|-------|----------|-------------|
| 702-06 | <b>Concrete Headwall Culvert End Treatment:</b> The contractor shall supply all labor and materials necessary to remove and install (2) concrete head wall on each side of culvert. Head walls are to be built per the detail shown in the plans and be constructed of 3000 psi Type M concrete with fiber mesh. The contractor shall pour monolithically with the new drive. All work shall be done in accordance with LA DOTD Standard Roads and Bridges, Section 702, 2016 Edition. The contractor shall dispose of both the headwall located on the west side of the drive and the second headwall located on the back side of the ditch and remove and all debris at no direct pay. |        |       | 2        | Each        |
| 701-05 | <b>15" A-2000 Culvert:</b> All labor and materials necessary to remove the existing culverts and provide and install 15" A-2000 culverts as indicated on the plan sheets. Item shall include cutting the ends of the pipe at a 45 degree angle and installing borrow to match end of pipe and the removal of both concrete and asphalt drives. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Sec. 701, 2016 Edition. All debris is to be removed at no direct pay.  |        |       | 158      | Linear Foot |
| 701-06 | <b>11" x 18" RCPA Culvert:</b> All labor and materials necessary to remove the existing culvert and provide and install 11" x 18" RCPA storm drains as indicated on the plan sheets. Item shall include removal of both concrete and asphalt drives. All pipe joints shall be wrapped with suitable geotextile fabric. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Sec. 701, 2016 Edition. All debris is to be removed at no direct pay.  |        |       | 96       | Linear Foot |
| S-001  | <b>Traffic Rated Trench Drain Steel Frame and Cover:</b> All labor and material necessary to provide and install an East Jordon bolt down, traffic rated trench drain steel frame and cover, model number 73810001 / 73810002 or approved equal. <b>Trench drain frame and cover sections are to 1' x 5' and the contractor shall provide enough material to span the existing width of the drives, cutting the extra frame and cover with a hand saw to fit the existing width of the drive.</b> Frames and covers fabricated by the contractor in house will not be accepted.  |        |       | 15'6"    | Linear Foot |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition

Starting at Sta. 00+00 at intersection of Ab's Rd. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description   | Length | Width | Quantity | Unit            |
|--------|---|--------|-------|----------|-----------------|
| 714-01 | <b>Sod:</b> All labor and materials necessary to install sod over the ends of the pipe to prevent erosion. Work shall be done in accordance to the LA DOTD Standard Specifications for Roads and Bridges, Sec. 714, 2016 Edition. All debris is to be removed at no direct pay. |        |       | 1        | <b>Lump Sum</b> |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition



## ST. TAMMANY PARISH

PATRICIA P. BRISTER  
PARISH PRESIDENT

**October 1, 2018**

Please find the following addendum to the below mentioned QUOTE.

**Addendum No.:** 1

**Quote#:** 312-00-18-26-1

**Project Name:** Windsor Dr. Drainage

**Quote Due Date:** Thursday, October 4, 2018

### **GENERAL INFORMATION:**

---

1. Please remove "Attachment A – Specifications" and replace with "Attachment A – Specifications REVISED." (Attached)

### **ATTACHMENTS:**

---

1. "Attachment A – Specifications REVISED.pdf"

**End of Addendum # 1**

Starting at Sta. 00+00 at intersection of Ab's Road. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description   | Length | Width | Quantity | Unit     |
|--------|---|--------|-------|----------|----------|
|        | <p><b>General Notes:</b></p> <ol style="list-style-type: none"> <li>1. Contractor shall field verify all quantities and measurements.</li> <li>2. Contractor shall be responsible for locating and protecting all existing utilities.</li> <li>3. Two-way traffic shall be maintained at all times during construction.</li> <li>4. Prior to beginning work, contractor shall furnish, erect and maintain project and construction signs in accordance with LA DOTD Standard Plans and Special Details Temporary Traffic Control.</li> <li>5. Driveway aprons shall be tied-in to existing hard surfaced drives or extend two (2) feet behind the culvert, whichever is greater. For clarification purposes, tie-in new asphalt to existing asphalt/concrete aprons at no direct pay.</li> <li>6. All turning radii shall be a minimum of thirty-five (35) feet.</li> <li>7. All existing sewer lines shall be tied-in at no direct pay.</li> <li>8. For clarification purposes, tie-in new asphalt to existing asphalt aprons at no direct pay on existing gravel roads.</li> <li>9. Any <i>additional work</i> performed by the contractor <i>without prior written approval</i> from the St Tammany Parish Department of Public Works, the cost of the work will be borne by the contractor and will not be reimbursed by the Parish.</li> </ol> |        |       |          |          |
|        | <p><b>Project Summary:</b> All labor and materials necessary to improve drainage by removing the existing culverts and replacing them with new culverts or trench drain at correct elevations as shown in the project drawings. Work shall also include replacing the drives with either asphalt or concrete, install 2 headwalls, sod at end of pipes and grade, shape, compact and pave end of street with (2) 2" lifts of asphalt.</p>   |        |       |          |          |
| 727-01 | <p><b>Mobilization:</b> All labor and materials necessary to accomplish preparatory work and operations, including those necessary for movement of personnel, equipment, supplies and incidentals to the project site.</p>  |        |       | 1        | Lump Sum |
| 713-01 | <p><b>Temporary Signs and Barricades:</b> All labor and materials necessary to furnish, install, maintain and remove temporary project signs, construction signs and/or barricades; providing flagmen; and complying with all other requirements regarding the protection of the work, workers and safety of the public. All items shall comply with plan details.</p> <p>All signs must be up prior to work starting for item to be paid.</p>  |        |       | 1        | Lump Sum |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition

Starting at Sta. 00+00 at intersection of Ab's Road. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description   | Length   | Width     | Quantity | Unit        |
|--------|---|--|-----------|----------|-------------|
| 306-01 | <b>Grade, Shape and Compact Road Bed:</b> Labor and materials necessary to grade, shape and compact existing gravel road to prepare for asphalt paving. Work shall include removal of excess rock to install base at correct elevation to receive 4" of asphalt paving. All work shall be done in accordance with the LA DOTD Standard Specifications for Roads and Bridges, Sec. 306, 2016 Edition. All debris shall be removed at no direct pay.  |  |           | 68       | Square Yard |
| 501-03 | <b>2" Asphalt Paving (LA DOTD Type 3):</b> All labor and materials necessary to provide and install 4" asphalt paving in 2 lifts. The contractor shall grade, shape and compact the existing stone base to allow for the installation of paving. All work shall be done in accordance with the LA DOTD Standard Specifications for Roads and Bridges, Section 501, 2000 Edition. The contractor shall saw cut along the existing edge of the pavement to provide a smooth, straight edge to pave along. All debris is to be removed at no direct pay.   | 1 <sup>st</sup> . 2" lift<br>2 <sup>nd</sup> 2" lift |           | 68<br>68 | Square Yard |
| 501-01 | <b>3" Asphalt Drive (LA DOTD Type 3):</b> All labor and materials necessary to install Asphalt driveway aprons and tie ins to existing drives. Driveway aprons on gravel/dirt drives shall be tied-in to existing hard surfaced drives or extend to the back edge of the ditch, whichever is greater. Aprons are to be installed per the LA DOTD Rural Drive Detail. Existing asphalt drives shall receive a new topping of asphalt and be extended to the back edge of the ditch if necessary. Transition aprons onto existing concrete drives are to be 18" minimum and shall be sealed where the edge tapers down to the existing hard surface drive to prevent unraveling. Sealer shall be applied with either a brush or roller and shall be 6' wide with three inches extending over the apron and three inches over the existing hard surface. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Section 501, 2000 Edition. All debris shall be removed at no direct pay. | 3 drives   | See Plans | 12       | Ton         |
| 706-03 | <b>6" Concrete Drive:</b> All labor and materials necessary to remove and replace existing concrete drive. The drive is to be constructed of 3000 psi Type M "High Early" concrete, 6" thick and shall have fiber mesh. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Section 706, 2016 Edition. All joint material shall be in kind and sealed with a product listed in the QPL. Work shall include all necessary saw cuts to remove the drive way panel. All debris shall be removed at no direct pay.   | 9 drives   | See Plans | 295      | Square Yard |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition



Starting at Sta. 00+00 at intersection of Ab's Road. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description  | Length | Width | Quantity | Unit        |
|--------|--|--------|-------|----------|-------------|
| 702-06 | <b>Concrete Headwall Culvert End Treatment:</b> The contractor shall supply all labor and materials necessary to remove and install (2) concrete head wall on each side of culvert. Head walls are to be built per the detail shown in the plans and be constructed of 3000 psi Type M concrete with fiber mesh. The contractor shall pour monolithically with the new drive. All work shall be done in accordance with LA DOTD Standard Roads and Bridges, Section 702, 2016 Edition. The contractor shall dispose of both the headwall located on the west side of the drive and the second headwall located on the back side of the ditch and remove and all debris at no direct pay. |        |       | 2        | Each        |
| 701-05 | <b>15" A-2000 Culvert:</b> All labor and materials necessary to remove the existing culverts and provide and install 15" A-2000 culverts as indicated on the plan sheets. Item shall include cutting the ends of the pipe at a 45 degree angle and installing borrow to match end of pipe and the removal of both concrete and asphalt drives. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Sec. 701, 2016 Edition. All debris is to be removed at no direct pay.  |        |       | 158      | Linear Foot |
| 701-06 | <b>11" x 18" RCPA Culvert:</b> All labor and materials necessary to remove the existing culvert and provide and install 11" x 18" RCPA storm drains as indicated on the plan sheets. Item shall include removal of both concrete and asphalt drives. All pipe joints shall be wrapped with suitable geotextile fabric. All work shall be done in accordance with LA DOTD Standard Specifications for Roads and Bridges, Sec. 701, 2016 Edition. All debris is to be removed at no direct pay.  |        |       | 96       | Linear Foot |
| S-001  | <b>Traffic Rated Trench Drain Steel Frame and Cover:</b> All labor and material necessary to provide and install an East Jordon bolt down, traffic rated trench drain steel frame and cover, model number 73810001 / 73810002 or approved equal. <b>Trench drain frame and cover sections are to 1' x 5' and the contractor shall provide enough material to span the existing width of the drives, cutting the extra frame and cover with a hand saw to fit the existing width of the drive.</b> Frames and covers fabricated by the contractor in house will not be accepted.  |        |       | 15'6"    | Linear Foot |

All Work Shall Conform to Louisiana Standard Specifications for Roads and Bridges, Latest Edition

Starting at Sta. 00+00 at intersection of Ab's Road. and ending at Sta. 07+37 at end of the project on Windsor Dr.

| Item   | Description   | Length | Width | Quantity | Unit     |
|--------|---|--------|-------|----------|----------|
| 714-01 | <b>Sod:</b> All labor and materials necessary to install sod over the ends of the pipe to prevent erosion. Work shall be done in accordance to the LA DOTD Standard Specifications for Roads and Bridges, Sec. 714, 2016 Edition. All debris is to be removed at no direct pay. |        |       | 1        | Lump Sum |